

APPLICATION FOR UNITED STATES PATENT

INVENTORS: **Anthony J. DeLuca**
 Richard J. Chenery Jr.

INVENTION: **TOOL SUPPORTING SYSTEM LOG FILE REPORTING**


DOCKET
NUMBER: RA 5428 (USYS.032PA)

CUSTOMER
NUMBER: 27516

Unisys Corporation
Charles A. Johnson
P O Box 64942 - MS 4773
St. Paul, MN 55164
Attorney for Applicant
Reg. No.: 20,852

SPECIFICATION

CERTIFICATE UNDER 37 CFR 1.10: The undersigned hereby certifies that this transmittal letter and the paper of papers, as described hereinabove, are being deposited in the United States Postal Service, "Express Mail Post Office to Addressee" having an Express Mail mailing label number of ET351442368US, in an envelope addressed to: ASSISTANT COMMISSIONER OF PATENTS, Washington, D.C. 20231 on the 21st day of December, 2001.


Charles A. Johnson

10087084-122101

TOOL SUPPORTING SYSTEM LOG FILE REPORTING

FIELD OF THE INVENTION

5 The present invention generally relates to tools that support performance analysis of computer systems, and more particularly to support of analyzing data logged in a system log file.

BACKGROUND OF THE INVENTION

10 Many computer systems host system software that logs various performance-related data to a log file. The log data include, for example, the number processor cycles consumed by a program, the quantity of system memory occupied and used by the program, input and output activity associated with the program and a variety of other information. In one example system, log data
15 records are sequentially written to the log file, with each entry pertaining to a particular program and including a timestamp that indicates the time at which the entry was written to the log file.

 One approach for accessing the system log file data is with a command-based user interface. With a command interface, a user can generate reports of
20 log file data using scripts of commands that are tailored to produce log data reports that meet the user's needs. The command-based approach requires the user to understand the syntax and functionality of the command language. For experienced users, the command-based approach may be acceptable. However, the trend toward graphical user interfaces that are intuitive may makes the
25 command-based approach seem difficult for new users.

 A method and apparatus that addresses the aforementioned problems, as well as other related problems, are therefore desirable.

SUMMARY OF THE INVENTION

30 In various embodiments, the present invention aids in report selection in a system that provides a plurality of reports. A database is populated with selected

data elements of a plurality of data types, and a database content table is created that indicates the data types of the data elements present in the database. For each report, a report identifier and an associated set of report requirements are established in a report table. Each set of report requirements identifies a set of data types required for the associated report. A set of report identifiers is output for the data types of data elements in the database that satisfy the associated sets of report requirements.

Various example embodiments are set forth in the Detailed Description and Claims which follow.

BRIEF DESCRIPTION OF THE DRAWINGS

Other aspects and advantages of the invention will become apparent upon review of the Detailed Description and upon reference to the drawings in which:

FIG. 1 is a functional block diagram of a computing arrangement for processing a system log file;

FIG. 2 illustrates an example user-interface screen for processing a log file;

FIG. 3 is a flowchart of an example process for creating a database table of selected log data from a log file;

FIG. 4 is a flowchart of an example process for assisting in report selection;

FIG. 5 is a screen dump of an example report template; and

FIG. 6 is a screen dump of an example listing of report names.

DETAILED DESCRIPTION

To eliminate the burden of having to learn a command language in order to report log file data, the system described below extracts log file data from a system log file and stores the log file data in a relational database. A graphical user interface (GUI) makes the data extraction process easy to learn. A GUI is also provided for generating reports from the data in the database.

In the example system for which the reporting mechanism is implemented, there are hundreds of log record types and subtypes. In addition

[illegible]

5

10

15

The extraction request is transmitted from log analyzer 122 to log access routine 110. The extraction request specifies, for example, types of records to read from the log file and a time interval that controls which records are read by the timestamps of the records. In response to an extraction request, the log access routine reads data from the specified log file (active or archived) and returns the data to the log analyzer. Various control data are exchanged between the log analyzer and the log access routine in processing the log data. For example, in one embodiment, the log analyzer opens a Telnet connection to system 102 and transfers a parameter file to the log access routine via FTP. The log access routine transfers the extracted data to the log analyzer via FTP.

Once the log data are extracted and indexed, reports can be generated for viewing by users. A user at client 124 interacts with report viewer 132 in

generating a report. Report files¹³⁴ define report templates that specify the type of log data and format for various reports. In one embodiment, Seagate Crystal Reports software is used in preparing the templates and generating the reports. The report viewer is a set of classes and functions made available by Seagate
5 Crystal Reports software. A DLL containing these classes and functions is referenced by the log analyzer and provides an interface to a report template and the capability to connect the indexed log data to the template. The generated report is displayed in a window, for example.

10 In the example embodiment, log data can be extracted on demand or as a batch service. Log analyzer batch service ¹³⁶ supports time delayed extraction of the log data.

The computing arrangement allows users to selectively extract from a system log file data that are of interest and store and index the log data in a database. once the log data are indexed and stored, various reports can be
15 generated by users without requiring further time-consuming access to the system log file.

FIG. 2 illustrates an example user-interface screen for processing a log file in accordance with another embodiment of the invention. The user-interface screen is shown to illustrate the type of information used to create a database of
20 log data. The *Log Description* field allows the user to associate with the database of log data a short textual description of the log data contained therein, and the *Log File Name* field allows the user to name the database of log data. The Options button includes fields that allow a user to specify an archived log file and also to specify appending the log data to the current log indexed log data ¹²⁸.
25 The user can alternatively specify creation of a new database.

The *Log Start Date*, *Log End Date*, *Log Start Time*, and *Log End Time* fields allow the user to specify the range of log file records that are to be extracted from the log file. Similarly, under the *Logs* tab the entries in the *Available Log*
30 *Types* list allow the user to further specify the criteria by which log records are extracted from the log file.

The *Acquire Now* button initiates immediate extraction of log data from the log file, and the *Batch* button registers with the log analyzer batch service 136 for extraction of the log data at a user-specified time. It will be appreciated that the specified *Available Log Types* are those associated with the 2200 series data
5 processing systems from Unisys. Different systems will have other system-specific types and formats of log data.

The CLASSES tab is an alternative way to specify log record types. The types of log records are categorized into different classes. Selection of a class of log record types results in extraction of all the log records of all the types that are
10 members of the selected class. The REPORTS tab enables selection of reports. Each report may involve a number of log record types.

FIG. 3 is a flowchart of an example process for creating a database table of selected log data from a log file. The log analyzer receives from a user a request to create a database of log data (step 302). The request includes, for example, a
15 time and date range, along with the type(s) of log data to read from the log file. In response to the request, the log analyzer connects to the log access routine of the host system and transmits the request (step 304).

The log access routine reads log data from the log file according to the selection criteria in the request (step 306). In one embodiment, the extracted log
20 data are accumulated in a file to be transferred to the log analyzer. The extracted log data are transmitted to the log analyzer (step 308).

The log analyzer converts the data from the log file format to a format suitable for loading in the database (step 310). In one embodiment, for example, the log data are converted to a file(s) of comma separated values ("CSV file"),
25 with log records separated by a carriage return. The values in the CSV file are textual data. The CSV format is useful for quickly loading the log data into the database (step 312). In one embodiment, the text file with the specified formatting is provided to an SQL BULK INSERT command. The field and record delimiters are input parameters to the INSERT command. It will be appreciated
30 that other delimiters may be used in other embodiments.

The conversion of the log data from the format of the log file to the format suitable for the database uses meta-data in the administrative database 130. The administrative database includes a single administrative table that identifies each field of each table that needs to be converted. A separate table is created for each type of log record. The key fields in the administrative table are the table name, starting location (relative to the first word/bit of the log record), length of the log record, and type of the log record. From this information, the data in the log file is located, converted to textual format, and written to a CSV file. There is a separate CSV file for each table. The data from the CSV file are then inserted in the proper table of the database 128.

Once the log data are available in the indexed database, various reports can be generated at users' requests. In one embodiment, the report templates defined by report files 134 are user-selectable and specify the type of log data needed for the report along with a report layout.

At step 314 a database content table is created that indicates which log record types are present in the database. Table 1 illustrates an example log-type table inside a log file database. The log-type table identifies the log types of the log records that are available in a log file database.

User Entry Info ID	Log Type	Log Sub Type	Log Description
1	71		System Time and Date Log
2	72		System Equipment Mnemonics Log
3	72		System Equipment Mnemonics Data
4	72		System Equipment Mnemonics Range Descriptor
5	73		System-ID Log
6	74		Log File Header Error Log
7	75		System Performance Log
8	101	1	Program Initiation
9	101	2	Program Continuation
10	101	3	Program Termination
11	102	1	Checkpoint Initiation
12	102	2	Restart Initiation
13	102	3	Checkpoint Termination
14	102	4	Restart Termination
15	103	1	TIP Program - 1. A multiple INITAL program has finished processing a message and has requested another. 2 A program has been restarted after processing a message. 3. A program has been stuck in memory after processing a message.
16	103	2	TIP program termination, the program has been removed from main storage after processing a message.

Table 1

Even though only one log file database is illustrated, in another embodiment users have the option of creating multiple log file databases. An associated database content table is created for each log file database.

FIG. 4 is a flowchart of an example process for assisting in report selection, and FIG. 5 is a screen dump of an example report template. For the reports that are defined by report templates in report files 134, the log analyzer creates a report description table in administrative database 130 (step 400). Table 2 below illustrates an example report description table.

Rep. ID	Report Name	Report Description	Report File Name	Report Category	Report Type
3	Log Entry Descriptor	Log Entry Descriptor Basic Report	LogDescriptor.rpt	General	Basic
4	System Log Type 071	System Time and Date	LogType-071.rpt	General	Basic
5	System Log Type 072	System Equipment Mnemonics	LogType-072.rpt	General	Basic
6	System Log Type 073	System ID	LogType-073.rpt	General	Basic
7	System Log Type 074	Log File Header Error	LogType-074.rpt	General	Basic
8	System Log Type 075	System Performance	LogType-075.rpt	General	Basic
9	Detailed Console Log Report	Detailed Console Log Report		None	Detailed
10	Detailed Qlink Report	Detailed Qlink Report		None	Detailed
11	Tape File Summary Report	Tape File Summary Report	Tape File Summary Report.rpt	Operations	Detailed
12	System Log Type 101	Program Log Entry	LogType-101.rpt	General	Basic
13	Device Usage Report	Measures use of peripheral devices: 107, 203, 301, 302, 403, 405		Facilities	Detailed
14	Equipment Usage Report	Equipment types that generated the log file: 108, 110		Debug	Detailed
15	Run Activity Trace Report	Analyze all run activity on the system: 101, 106, 107	Run-Program Activity Trace Report.rpt	Debug	Detailed
17	File List	Detail of all cataloged files used: 107, 403, 405		None-File	Detailed
18	ROLOUT report	Detail of all ROLOUT activity: 101, 106, 107, 302, 403, 405	Rolout Report.rpt	Operations	Detailed
19	ROLBAK Report	Detail of all ROLBAK activity: 101, 106, 107, 302, 403, 405	Rolbak Report.rpt	Operations	Detailed
20	File Access Report	All files accessed with runid and time accessed: 106, 107, 403	File Access Report.rpt	Operations	Detailed
21	File Rename Report	Detail of all cataloged files that had name changes: 408	File Rename Report.rpt	Operations	Detailed

Table 2

The report description table includes for each report template a report identifier, a report name, a textual description of the report, the name of the template file that defines the report, a category for classifying reports, a type field for classifying the report according to level of detail provided by the report, and other implementation-specific information.

The log analyzer also creates a report requirements table that specifies the log record types that are required for the different reports (step 402). Table 3 below illustrates a subset of entries in an example report requirements table for the reports described in Table 2.

10

RepLog ID	Report ID	Log Type ID
5	12	7
6	12	8
7	12	9
9	6	4
10	7	5
11	8	6
16	68	7
17	68	8
18	68	9
19	80	7
20	80	8

Table 3

The RepLog ID field is used to uniquely identify each row in the table. The report ID is the report identifier from Table 2, and the Log Type ID field identifies the log record type required for the report (indexes Table 4 below).

15

Table 4 describes the types of log records. Table 3 identifies the log type identifiers that are required for a report, Table 4 indicates the log types associated with the log type identifiers, and Table 1 indicates the log types that are present in the database.

Log Type ID	Log Type	Log Sub Type	Log Name	Log Table Name	Log Description	Log Field Count	Sub Table
1	71		Log File Header	071 - System Time and Date	System Time and Date Log	9	NO
2	72		Log File Header	072 - System Equipment Mnemonics	System Equipment Mnemonics Log	4	NO
3	72		Log File Header	072 - System Equipment Mnemonics Data	System Equipment Mnemonics Data	3	YES
229	72		Log File Header	072 - System Equipment Mnemonics Range Descriptor	System Equipment Mnemonics Range Descriptor	5	YES
4	73		Log File Header	073 - System-ID	System-ID Log	13	NO
5	74		Log File Header	074 - Log File Header Error	Log File Header Error Log	4	NO
6	75		Log File Header	075 - System Performance	System Performance Log	4	NO
7	101	1	Accounting	101 - Program Log Entry	Program Initiation	79	NO
8	101	2	Accounting	101 - Program Log Entry	Program Continuation	79	NO
9	101	3	Accounting	101 - Program Log Entry	Program Termination	79	NO
10	102	1	Accounting	102 - Checkpoint Restart	Checkpoint Initiation	37	NO
11	102	2	Accounting	102 - Checkpoint Restart	Restart Initiation	37	NO
12	102	3	Accounting	102 - Checkpoint Restart	Checkpoint Termination	37	NO

Table 4

After a user has created a log file database (FIG. 3), the user has the option of displaying various reports of the log data. For example, to initiate reporting

functions, the user selects the REPORTS tab of the interface screen of FIG. 2, effectively providing a request to the log analyzer to provide a list of available reports (step 404).

To fulfill the request, the log analyzer gets the database content table
5 (Table 1) from the administrative database 130 (step 406). The log analyzer then identifies (step 408) which reports have report requirements that are satisfied by the log file database. That is, for each Report ID in the report description table, the necessary log type IDs are obtained from the report requirements table. If for
10 a report all the log type IDs are present in the database content table, the associated report name is one of the report names in the list displayed for the user (step 410). FIG. 6 is a screen dump in which report names are displayed for a log file having only log records of log record type 101. Only those reports that are supported by this log record type are shown.

In one embodiment, the report names displayed to the user are user
15 selectable. In response to selection of a report name, report viewer 132 reads the necessary log file data from database 128 and displays the data to the user.

Accordingly, the present invention provides, among other aspects, a method and apparatus for a tool that support log file reporting. Other aspects and embodiments of the present invention will be apparent to those skilled in the
20 art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and illustrated embodiments be considered as examples only, with a true scope and spirit of the invention being indicated by the following claims.

25